Amendments to the Specification

IN THE WRITTEN DESCRIPTION

Please replace the paragraph beginning at page 5, line 27, with the following rewritten paragraph:

Fig. 1 shows the holding device 1 in a cross-sectional view. The holding device comprises a shuttering device 2, which is preferably made of steel and has a U-shaped cross-section. This U-shaped cross-section can be easily seen in Figure 2 and is formed by a cover wall 3 and legs 4 adjoining at both sides and extending in parallel. The shuttering device 2 rests on a surface 6 of a shuttering support 7 with supporting surfaces 5. The shuttering support 7 is preferably made of steel and is preferably part of a shuttering table.

Please replace the paragraph beginning at page 6, line 17, with the following rewritten paragraph:

Furthermore, the magnet comprises a support device 13 securely connected to the magnet and having a stop 14. The stop can be engaged with the cover wall 3 of the shuttering device 2. In the representation according to Figure 1, the stop 14stop 4, however, is not engaged with the cover wall. Such an engagement is only effected if the magnet projects with respect to the supporting surfaces 5 of the shuttering device 2. Here, an angle of rotation of approx. 3° to 5° with respect to the position represented in Figure 1 is sufficient. The stop 14 is then engaged with the cover wall 3 or is supported at the same, respectively.